

### **SNOW REMOVAL** For Skid Steers, Utility Loaders, Wheel Loaders, & Backhoe Loaders





Paladin Attachments provides a variety of snow removal attachments that will get the job done right.

Whether you are a large property owner, business owner, farmer, snow removal professional, or just need to move a lot of snow, we have every essential snow attachment you will ever need. Look to Paladin as your one stop shop for high quality Snow Blowers, Snow Pushes, Snow Blades, V-Blade Plows, and Snow Buckets. We also feature angle sweepers and walk behind sweepers. As always, we cover all the prime movers including compact tool carriers, skid steer loaders, compact tractors, utility tractors, backhoe loaders, and wheel loaders (compact to full size).

- 1 year warranty on structure
- 6 month warranty on hydraulics •











# **Snow Pushes**

The FFC **Snow Push**, by Paladin is engineered of heavyduty, fully welded steel with 3/8" thick end plates to capture and remove even the heaviest snow without leaving windrows or spillover. For SSL, Compact Utility Loaders, Small Wheel Loaders and Backhoe Loaders.

- Moves large volumes of snow efficiently.
- Rubber edge standard on all models.
- Ideal for waste water, manure, feed lot and food cleanup.
- Optional Pull Back Kit draws back snow from buildings, fences and confined areas.









228 Series (4 ft x 4 ft) Snow Push Specifications									
Model	Path Width	Working Height	Depth	Overall Width	Weight (approx)				
22812	142.5"	48.8"	71.8"	149.7"	2485				
22814	166.5"	48.8"	71.8"	173.7"	2660				
22816	190.5"	48.8"	71.8"	197.7"	2835				
22820	238.5"	48.8"	71.8"	245.7"	3185				

Carrier Specifications: Lift Capacity: <9,500 lbs; Operating Weight <30,000 lbs

232 Series (Low Profile) Snow Push Specifications									
Model	Path Width	Working Height	Depth	Overall Width	Weight (approx)				
23272-0022	71.5"	23.7"	38.1"	77.3"	525 lbs				
23284-0022	83.5"	23.7"	38.1"	89.3"	570 lbs				
23296-0022	95.5"	23.7"	38.1"	101.3"	610 lbs				
23220-0022	119.5"	23.7"	38.1"	125.3"	705 lbs				

Carrier Specifications: Lift Capacity: <9,500 lbs; Operating Weight <11,500 lbs

233 Series (3ft x 3ft) Snow Push Specifications									
Model	Path Width	Working Height	Depth	Overall Width	Weight (approx)				
23396	95.5"	41.3"	41.5"	101.5"	1100 lbs				
23320	119.5"	41.3"	41.5"	125.5"	1230 lbs				
23344	143.5"	41.3"	41.5"	149.5"	1375 lbs				
23368	167.5"	41.3"	41.5"	173.5"	1505 lbs				

Carrier Specifications: Lift Capacity: <11,000 lbs; Operating Weight <20,000 lbs

#### www.paladinattachments.com

## **Compact Tractor Snow Pushes**



FFC also features **Compact Tractor Snow Pushes** designed to mount on tractor frontend loaders with universal skid steer style mountings. Lift capacity of the loader should be less than 2,000 lbs. These snow pushes have side wearing skids and a rubber cutting edge.

Compact Tractor Snow Push Specifications									
Model	Path Width	Working Height	Depth	Overall Width	Weight (approx)				
10707-60-0822	61.8"	30.8"	34"	62.3"	415 lbs				
10707-72-0822	73.8"	30.8"	34"	74.3"	450 lbs				
10707-84-0822	85.8"	30.8"	34"	86.3"	484 lbs				
10707-96-0822	97.8"	30.8"	34"	98.3"	518 lbs				

Carrier Specifications: Lift Capacity: <2,000 lbs; Operating Weight <4,000 lbs



Compact Tractor Tri	p Edge Model	s Snow Pus	h Specificat	ions	
Model	Path Width	Working Height	Depth	Overall Width	Weight (approx)
10709-78-0822	72.9"	39.8"	44.1"	80.4"	850 lbs
10709-96-0822	90.9"	39.8"	44.1"	98.4"	930 lbs
10709-08-0822	102.9"	39.8"	44.1"	110.4"	990 lbs
10709-20-0822	112.4"	39.8"	44.1"	119.9"	1030 lbs



Carrier Specifications: Lift Capacity: <4,000 lbs; Operating Weight <8,000 lbs



## **Snow Blades**

The **114 Series Snow Blade** is available in either hydraulic or manual angle. For Skid Steers, Compact Tool Carriers, and Compact Utility Loaders.

- Hydraulically angles 30° in either direction
- Reversible and replaceable wear edge
- Adjustable skid-shoes
- Spring-loaded trip mechanism
- 23" 7-gauge steel blade
- Heavy structural steel frame
- Standard hydraulic angle
- Optional manual angle
- Optional rubber wear edge

The **5700 Series** angles 30° in either direction hydraulically. Blade us made from reinforced ten gauge steel. For SSL, Compact Utility Loaders, and Backhoe Loaders.

- Reversible and replaceable wear edge
- Adjustable skid shoes
- Spring-loaded trip mechanism
- Heavy structural steel frame
- Standard hydraulic angle
- Optional rubber wear edge





Specifications 114 Series									
Model	Weight (approx)	Width OD	Height OD	Cutting Width @ Max Angle					
11448	460 lbs	48"	23"	41.5"					
11460	510 lbs	60"	23"	52"					
11472	595 lbs	72"	23"	62"					
11484	635 lbs	84"	23"	73"					
11496	650 lbs	96"	23"	83"					

Carrier Specifications: lift capacities <5,000 lbs operating weight <8,000 lbs

Specifications 5700 Series								
Model	Weight (approx)	Width	Height	Cutting Width @ 30° Angle				
LAF5784	875 lbs	84"	32"	73"				
LAF5796	930 lbs	96"	32"	83"				
LAF5708	890 lbs	108"	32"	93"				
LAF5720	1065 lbs	120"	32"	104"				
LAF5732	1125 lbs	132"	32"	114"				
LAF5744	1185 lbs	144"	32"	125"				

Carrier Specifications: lift capacities <9,000 lbs operating weight <11,000 lbs

#### www.paladinattachments.com

### **Snow Blades**



Specifications 115 Series								
Model	Weight (approx)	Width	Height	Cutting Width @ 35° Angle				
11584	1125 lbs	84"	32"	69"				
11596	1180 lbs	96"	32"	79"				
11508	1235 lbs	108"	32"	88"				
11520	1315 lbs	120"	32"	98"				
11532	1375 lbs	132"	32"	108"				
11544	1435 lbs	144"	32"	118"				

Carrier Specifications: lift capacities <11,000 lbs operating weight <20,000 lbs

Specifications 136 Series									
Model	Weight (approx)	Width	Height	Depth	Cutting Width @ 30° Angle				
13684	940 lbs	84"	33"	42"	73"				
13696	990 lbs	96"	33"	42"	83"				
13608	1030 lbs	108"	33"	42"	93.5"				

Carrier Specifications: lift capacities <9,000 lbs operating weight <11,000 lbs

The **115 Series** angles 35° in either direction hydraulically. Equipped with a 7-gauge steel blade. Optional flap reduces snow spillage. For Large SSL, Compact Utility Loaders, Small Wheel Loaders and Backhoe Loaders.

- Replaceable wear edge (optional rubber edge)
- Adjustable skid shoes
- Spring-loaded trip mechanism

The **136 Series** has a cutting edge trip system that allows operator to glide over manholes and curb obstructions without losing gathered material. For skid-steers.

- Angles 30° in either direction hydraulically
- Reversible high carbon steel bolt-on edge
- 5° floating tilt allows for cleaner snow removal



IMPORTANT: All replacement hydraulic hoses and fittings must have a minimum rated working pressure of 4000 psi. Hoses and hydraulic couplers from the attachment to the loader are included for skid-steer only.



### **Snow Blowers**

FFC **Snow Blowers**, by Paladin feature a two-stage hydraulic blower that throws snow up to 45 ft. Blower is electrically controlled, and has hydraulically operated poly-lined chute and deflector. Equipped with reinforced wrapper and adjustable skid shoes. Case drains are not required for high-flow models. Has replaceable wear resistant steel tapered wear edge and high-volume 25" or 36" shroud opening. For Skid Steer Loaders and Compact Tool Carriers.

There is an optional Truck Chute Kit for snow blower models 11072G, 11072H, 11078G, 11078H, 11084G, 11084H, 11096G, and 11096H.

When ordering, verify hydraulic flow and pressure of skid-steer. Failure to supply proper flow and pressure could result in motor failure or poor performance.









Model # (Approx)Cutting WidthCutting heightDepth HeightHeight MotorsAuger MotorsFan Dia.PSI RangeGPM RangeHose RangeStandar-FiveMotors745 lbs48"25"38"57"Single14"18"200-30008-1450"110600795 lbs60"25"38"57"Single14"18"200-300014-2150"110600795 lbs60"25"38"57"Single14"18"200-300014-2150"110601795 lbs60"25"38"57"Single14"18"200-300014-2150"110602795 lbs60"25"38"57"Single14"18"200-300014-2150"110720845 lbs72"25"38"57"Single14"18"200-300014-2150"110721845 lbs72"25"38"57"Single14"18"200-300014-2150"110784878 lbs78"25"38"57"Single14"18"200-300014-2150"110784895 lbs84"25"38"57"Single14"18"200-300014-2150"110784895 lbs84"25"38"57"Single14"18"200-300014-2150"110845895 lbs84"25"38"<	Specifications											
11048A   745 lbs   48"   25"   38"   57"   Single   14"   18"   2000-3000   8-14   .50"     11060C   795 lbs   60"   25"   38"   57"   Single   14"   18"   2000-3000   12-17   .50"     11060D   795 lbs   60"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11060E   795 lbs   60"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11060E   795 lbs   60"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11072D   845 lbs   72"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11072E   845 lbs   78"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11078D   878 lbs   78"   25"   38"   57"   Single   14"	Model #	-	-	-	Depth	Height		-		PSI Range		
11060C     795 lbs     60"     25"     38"     57"     Single     14"     18"     2000-3000     12-17     .50"       11060D     795 lbs     60"     25"     38"     57"     Single     14"     18"     2000-3000     14-21     .50"       11060E     795 lbs     60"     25"     38"     57"     Single     14"     18"     2000-3000     14-21     .50"       11060E     795 lbs     60"     25"     38"     57"     Single     14"     18"     2000-3000     14-21     .50"       11072D     845 lbs     72"     25"     38"     57"     Single     14"     18"     2000-3000     14-21     .50"       11072E     845 lbs     72"     25"     38"     57"     Single     14"     18"     2000-3000     14-21     .50"       11078E     878 lbs     78"     25"     38"     57"     Single     14"     18"     2000-3000     14-21     .50"	Standard-Flow Models											
11060D     795 lbs     60"     25"     38"     57"     Single     14"     18"     2000-3000     14-21     .50"       11060E     795 lbs     60"     25"     38"     57"     Single     14"     18"     2000-3000     18-27     .50"       11072D     845 lbs     72"     25"     38"     57"     Single     14"     18"     2000-3000     14-21     .50"       11072D     845 lbs     72"     25"     38"     57"     Single     14"     18"     2000-3000     14-21     .50"       11072E     845 lbs     72"     25"     38"     57"     Single     14"     18"     2000-3000     14-21     .50"       11078E     878 lbs     78"     25"     38"     57"     Single     14"     18"     2000-3000     14-21     .50"       11078E     878 lbs     78"     25"     38"     57"     Single     14"     18"     2000-3000     14-21     .50"	11048A	745 lbs	48"	25"	38"	57"	Single	14"	18"	2000-3000	8-14	.50"
11060E     795 lbs     60"     25"     38"     57"     Single     14"     18"     2000-3000     18-27     .50"       11072D     845 lbs     72"     25"     38"     57"     Single     14"     18"     2000-3000     14-21     .50"       11072D     845 lbs     72"     25"     38"     57"     Single     14"     18"     2000-3000     14-21     .50"       11072E     845 lbs     72"     25"     38"     57"     Single     14"     18"     2000-3000     14-21     .50"       11078D     878 lbs     78"     25"     38"     57"     Single     14"     18"     2000-3000     14-21     .50"       11078E     878 lbs     78"     25"     38"     57"     Single     14"     18"     2000-3000     14-21     .50"       11074E     895 lbs     84"     25"     38"     57"     Single     14"     18"     200-3000     14-21     .50"	11060C	795 lbs	60"	25"	38"	57"	Single	14"	18"	2000-3000	12-17	.50"
11072D   845 lbs   72"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11072E   845 lbs   72"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11072E   845 lbs   72"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11078D   878 lbs   78"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11078E   878 lbs   78"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11078E   878 lbs   78"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11084D   895 lbs   84"   25"   38"   57"   Single   14"   18"   2000-3000   18-27   .50"     11072F   1150 lbs   72"   36"   43"   74"   Single   18"2	11060D	795 lbs	60"	25"	38"	57"	Single	14"	18"	2000-3000	14-21	.50"
11072E   845 lbs   72"   25"   38"   57"   Single   14"   18"   2000-3000   18-27   .50"     11078D   878 lbs   78"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11078D   878 lbs   78"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11078L   878 lbs   78"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11078L   878 lbs   78"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11084D   895 lbs   84"   25"   38"   57"   Single   14"   18"   2000-3000   18-27   .50"     11084E   895 lbs   84"   25"   38"   57"   Single   14"   18"   2000-3000   18-27   .50"     11072F   1150 lbs   72"   36"   43"   74"   Dual   18"	11060E	795 lbs	60"	25"	38"	57"	Single	14"	18"	2000-3000	18-27	.50"
11078D   878 lbs   78"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11078E   878 lbs   78"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11078E   878 lbs   78"   25"   38"   57"   Single   14"   18"   2000-3000   18-27   .50"     11084D   895 lbs   84"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11084E   895 lbs   84"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11084E   895 lbs   84"   25"   38"   57"   Single   14"   18"   2000-3000   18-27   .50"     11084E   895 lbs   84"   26"   2500-3500   18-27   .50"     11072F   1150 lbs   72"   36"   43"   74"   Dual   18"   26"   2500-3500   19-34   .75"  <	11072D	845 lbs	72"	25"	38"	57"	Single	14"	18"	2000-3000	14-21	.50"
11078E   878 lbs   78"   25"   38"   57"   Single   14"   18"   2000-3000   18-27   .50"     11084D   895 lbs   84"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11084E   895 lbs   84"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11084E   895 lbs   84"   25"   38"   57"   Single   14"   18"   2000-3000   18-27   .50"     11084E   895 lbs   84"   25"   38"   57"   Single   14"   18"   2000-3000   18-27   .50"     High-Flow Models     11072F   1150 lbs   72"   36"   43"   74"   Dual   18"   26"   2500-3500   22-34   .75"     11072G   1160 lbs   72"   36"   43"   74"   Dual   18"   26"   2500-3500   30-42   .75"     11072H   1160 lbs   78"   36"	11072E	845 lbs	72"	25"	38"	57"	Single	14"	18"	2000-3000	18-27	.50"
11084D   895 lbs   84"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11084E   895 lbs   84"   25"   38"   57"   Single   14"   18"   2000-3000   14-21   .50"     11084E   895 lbs   84"   25"   38"   57"   Single   14"   18"   2000-3000   18-27   .50"     High-Flow Models     High-Flow Models     11072F   1150 lbs   72"   36"   43"   74"   Single   18"   26"   2500-3500   22-34   .75"     11072G   1160 lbs   72"   36"   43"   74"   Dual   18"   26"   2500-3500   19-34   .75"     11072H   1160 lbs   72"   36"   43"   74"   Dual   18"   26"   2500-3500   30-42   .75"     11072H   1160 lbs   78"   36"   43"   74"   Dual   18"   26"   2500-3500   22-34   .75"     11078F   1200 lb	11078D	878 lbs	78"	25"	38"	57"	Single	14"	18"	2000-3000	14-21	.50"
11084E   895 lbs   84"   25"   38"   57"   Single   14"   18"   2000-3000   18-27   .50"     High-Flow Models     11072F   1150 lbs   72"   36"   43"   74"   Single   18"   26"   2500-3500   22-34   .75"     11072G   1160 lbs   72"   36"   43"   74"   Dual   18"   26"   2500-3500   22-34   .75"     11072G   1160 lbs   72"   36"   43"   74"   Dual   18"   26"   2500-3500   19-34   .75"     11072H   1160 lbs   72"   36"   43"   74"   Dual   18"   26"   2500-3500   30-42   .75"     11072H   1160 lbs   72"   36"   43"   74"   Dual   18"   26"   2500-3500   30-42   .75"     11078F   1200 lbs   78"   36"   43"   74"   Dual   18"   26"   2500-3500   19-34   .75"     11078H   1200 lbs   78"   36"   43"	11078E	878 lbs	78"	25"	38"	57"	Single	14"	18"	2000-3000	18-27	.50"
High-Flow Models       11072F     1150 lbs     72"     36"     43"     74"     Single     18"     26"     2500-3500     22-34     .75"       11072G     1160 lbs     72"     36"     43"     74"     Dual     18"     26"     2500-3500     19-34     .75"       11072G     1160 lbs     72"     36"     43"     74"     Dual     18"     26"     2500-3500     19-34     .75"       11072H     1160 lbs     72"     36"     43"     74"     Dual     18"     26"     2500-3500     30-42     .75"       11072H     1160 lbs     72"     36"     43"     74"     Dual     18"     26"     2500-3500     30-42     .75"       11078F     1200 lbs     78"     36"     43"     74"     Dual     18"     26"     2500-3500     22-34     .75"       11078G     1200 lbs     78"     36"     43"     74"     Dual     18"     26"     2500-3500     <	11084D	895 lbs	84"	25"	38"	57"	Single	14"	18"	2000-3000	14-21	.50"
11072F1150 lbs72"36"43"74"Single18"26"2500-350022-34.75"11072G1160 lbs72"36"43"74"Dual18"26"2500-350019-34.75"11072H1160 lbs72"36"43"74"Dual18"26"2500-350030-42.75"11072H1160 lbs72"36"43"74"Dual18"26"2500-350030-42.75"11078F1200 lbs78"36"43"74"Single18"26"2500-350022-34.75"11078G1200 lbs78"36"43"74"Dual18"26"2500-350019-34.75"11078H1200 lbs78"36"43"74"Dual18"26"2500-350030-42.75"11078H1200 lbs78"36"43"74"Dual18"26"2500-350030-42.75"11084F1190 lbs84"36"43"74"Single18"26"2500-350022-34.75"	11084E	895 lbs	84"	25"	38"	57"	Single	14"	18"	2000-3000	18-27	.50"
11072G     1160 lbs     72"     36"     43"     74"     Dual     18"     26"     2500-3500     19-34     .75"       11072H     1160 lbs     72"     36"     43"     74"     Dual     18"     26"     2500-3500     19-34     .75"       11072H     1160 lbs     72"     36"     43"     74"     Dual     18"     26"     2500-3500     30-42     .75"       11078F     1200 lbs     78"     36"     43"     74"     Dual     18"     26"     2500-3500     22-34     .75"       11078G     1200 lbs     78"     36"     43"     74"     Dual     18"     26"     2500-3500     22-34     .75"       11078G     1200 lbs     78"     36"     43"     74"     Dual     18"     26"     2500-3500     19-34     .75"       11078H     1200 lbs     78"     36"     43"     74"     Dual     18"     26"     2500-3500     30-42     .75"	High-Flow	High-Flow Models										
11072H1160 lbs72"36"43"74"Dual18"26"2500-350030-42.75"11078F1200 lbs78"36"43"74"Single18"26"2500-350022-34.75"11078G1200 lbs78"36"43"74"Dual18"26"2500-350019-34.75"11078H1200 lbs78"36"43"74"Dual18"26"2500-350019-34.75"11078H1200 lbs78"36"43"74"Dual18"26"2500-350030-42.75"11084F1190 lbs84"36"43"74"Single18"26"2500-350022-34.75"	11072F	1150 lbs	72"	36"	43"	74"	Single	18"	26"	2500-3500	22-34	.75"
11078F   1200 lbs   78"   36"   43"   74"   Single   18"   26"   2500-3500   22-34   .75"     11078G   1200 lbs   78"   36"   43"   74"   Dual   18"   26"   2500-3500   19-34   .75"     11078G   1200 lbs   78"   36"   43"   74"   Dual   18"   26"   2500-3500   19-34   .75"     11078H   1200 lbs   78"   36"   43"   74"   Dual   18"   26"   2500-3500   30-42   .75"     11078H   1200 lbs   78"   36"   43"   74"   Dual   18"   26"   2500-3500   30-42   .75"     11084F   1190 lbs   84"   36"   43"   74"   Single   18"   26"   2500-3500   22-34   .75"	11072G	1160 lbs	72"	36"	43"	74"	Dual	18"	26"	2500-3500	19-34	.75"
11078G     1200 lbs     78"     36"     43"     74"     Dual     18"     26"     2500-3500     19-34     .75"       11078H     1200 lbs     78"     36"     43"     74"     Dual     18"     26"     2500-3500     19-34     .75"       11078H     1200 lbs     78"     36"     43"     74"     Dual     18"     26"     2500-3500     30-42     .75"       11084F     1190 lbs     84"     36"     43"     74"     Single     18"     26"     2500-3500     22-34     .75"	11072H	1160 lbs	72"	36"	43"	74"	Dual	18"	26"	2500-3500	30-42	.75"
11078H     1200 lbs     78"     36"     43"     74"     Dual     18"     26"     2500-3500     30-42     .75"       11084F     1190 lbs     84"     36"     43"     74"     Single     18"     26"     2500-3500     30-42     .75"	11078F	1200 lbs	78"	36"	43"	74"	Single	18"	26"	2500-3500	22-34	.75"
11084F 1190 lbs 84" 36" 43" 74" Single 18" 26" 2500-3500 22-34 .75"	11078G	1200 lbs	78"	36"	43"	74"	Dual	18"	26"	2500-3500	19-34	.75"
	11078H	1200 lbs	78"	36"	43"	74"	Dual	18"	26"	2500-3500	30-42	.75"
11084G 1240 lbs 84" 36" 43" 74" Dual 18" 26" 2500-3500 19-34 .75"	11084F	1190 lbs	84"	36"	43"	74"	Single	18"	26"	2500-3500	22-34	.75"
	11084G	1240 lbs	84"	36"	43"	74"	Dual	18"	26"	2500-3500	19-34	.75"
11084H     1240 lbs     84"     36"     43"     74"     Dual     18"     26"     2500-3500     30-42     .75"	11084H	1240 lbs	84"	36"	43"	74"	Dual	18"	26"	2500-3500	30-42	.75"
11096G     1320 lbs     96"     36"     43"     74"     Dual     18"     26"     2500-3500     19-34     .75"	11096G	1320 lbs	96"	36"	43"	74"	Dual	18"	26"	2500-3500	19-34	.75"
11096H     1320 lbs     96"     36"     43"     74"     Dual     18"     26"     2500-3500     30-42     .75"	11096H	1320 lbs	96"	36"	43"	74"	Dual	18"	26"	2500-3500	30-42	.75"

Carrier Specifications: lift capacities <9,500 lbs operating weight <11,000 lbs

#### www.paladinattachments.com

### **Snow Buckets**



**Snow Buckets** move large volumes of snow or other loose materials efficiently. Equipped with a cut out back plate for better visibility. Quickly attaches to all skid-steer, backhoe, utility loader and small wheel loader brands. Optional Bolt on edge available. For SSL, Compact Utility Loaders, Compact Wheel Loaders, and Backhoe Loaders

Specifications							
Model	Weight Approx	Width	Height A	Depth B	Leading Edge C	Capacity Struck	Capacity Heaped
11184 <sup>1</sup>	733 lbs	84"	29.9"	42.0"	29.7"	1.14 yd³	1.47 yd³
11196 <sup>1</sup>	795 lbs	96"	29.9"	42.0"	29.7"	1.31 yd³	1.70 yd³
11197 <sup>1</sup>	999 lbs	96"	37.6"	46.2"	32.5"	1.83 yd³	2.36 yd <sup>3</sup>
11101 <sup>2</sup>	820 lbs	101.5"	29.9"	42.0"	29.7"	1.40 yd³	1.82 yd³
11102 <sup>2</sup>	1020 lbs	101.5"	37.6"	46.2"	32.5"	1.95 yd³	2.52 yd <sup>3</sup>
111082	1078 lbs	108"	37.6"	46.2"	32.5"	2.07 yd <sup>3</sup>	2.67 yd³



<sup>1</sup>Med. Duty Bucket

 $\label{eq:carrier Specifications: lift capacities < 5,000 \ \mbox{lbs operating weight} < 8,000 \ \mbox{lbs}$ 

<sup>2</sup>Heavy Duty Bucket

Carrier Specifications: lift capacities <9,500 lbs operating weight <11,000 lbs



# V-Blade Snow Plows

A multi-function blade for removal of snow from walks, driveways, or parking lots. Five position adjustable blade adds versatility for your snow removal needs and allows you to get the job done fast!

- Available in six blade widths 60", 72", 84", 96", 108", 120"
- Available with hydraulic sequencing valve or electro-hydraulic valve for independent blade function
- Adjustable blade allows for the following positions:
  - Straight
  - V
  - Scoop
  - Angles up to 30° in both directions
- Reversible cutting edge designed with spring loaded trip mechanism
- Blade floats 5° and tilts 5° for ground contour
- Adjustable skid shoes
- Optional polyurethane cutting edge
- 32.5" blade height
- Universal skid-steer loader quick attach mounting













Specifications						
Model	Weight (Approx)	Height	Width (Straight)	Cutting Width at Full "V"	Cutting Width at Full "Scoop"	Cutting Width at Max Angle (30°)
12060	865 lbs	32.5"	60"	56"	48"	52"
12072	920 lbs	32.5"	72"	66.5"	58.5"	62.5"
12084	975 lbs	32.5"	84"	77"	69"	73"
12096	1020 lbs	32.5"	96"	87.5"	79.5"	83.5"
12008	1060 lbs	32.5"	108"	98"	90"	94"
12020	1110 lbs	32.5"	120"	108"	100.5"	104"

For more information about Paladin's full range of snow removal attachments, contact us at the number below. Don't forget to ask about our range of angle brooms and walk-behind sweepers for your snow removal needs.

You Tube



Subject to change without notice.

in